



ProSeries[™]

SIDE-MOUNT SAND FILTERS

Minimal maintenance for added convenience.

Hayward ProSeries sand filters deliver crystal clear water through advanced pool filter technology for pools of all types and sizes. And, since this sand filter requires minimal care, users will appreciate its added convenience.

The durable housing is molded of corrosion-proof polymeric materials. Additional features include an advanced, self-cleaning lateral system for smooth, efficient flow and totally balanced backwashing. Plus, with a Hayward 6-position Vari-Flo[™] control valve, you can quickly dial any of the valve/filter functions for easier operation and maximum efficiency.



Manual Air Relief

for easy, manual release of air from system.

Durable Flanged Inspection/Access Cover

provides convenient access to top of filter.

Unitized, Corrosion-Proof Filter Tank


molded of tough, durable, color-fast polymeric material for dependable all-weather performance.

Efficient, Multilateral Underdrain Assembly

with 360° slotted, self-cleaning laterals, gives totally balanced flow and backwashing.

Integral Molded Drain Plug

for easy draining of tank, without the loss of sand.



Integral Top Diffuser

ensures even distribution of water over the top of the sand media bed. All internal plumbing is 2" for superior hydraulic performance.

Hayward 6-Position Vari-Flo™ Control Valve

with easy-to-use lever-action handle lets you dial any of the six valve/filter functions. Integral sight glass lets you see when backwash cycle is completed.

Totally Corrosion-Proof Base

is rugged and attractively styled to provide strong, stable support.

SPECIFICATIONS – PRO SERIES SIDE-MOUNT SAND FILTERS

| | |
|-------------------|---|
| FILTER TYPE | High-Rate Sand: No. ½ Silica Sand (0.45 mm – 0.55 mm) |
| FILTER TANK | Molded Polymeric |
| UNDERDRAIN | 360° Slotted Self-Cleaning Slotted Laterals, Precision-Installed in Ball Joint Assembly |
| CONTROL VALVE | 1½" or 2", 6-Position Vari-Flo or 2", 2-Position Slide Valve. May also be plumbed singularly or in series with quick disconnect union couplings (less valve). |
| SUPPORT BASE | Injection-Molded Polymer |
| PERFORMANCE RANGE | 30 to 120 GPM, 114 to 454 LPM |
| DIMENSIONS | S210S – 20½" W x 32½" H (52 cm x 82 cm) S244S – 24½" W x 36" H (62 cm x 91 cm) S310S – 30½" W x 40" H (78 cm x 104 cm) |




Vari-Flo 6-Position Control Valve

The easy-to-use lever action lets you "dial" any of six valve/filter functions.

PERFORMANCE DATA

| MODEL NUMBER | EFFECTIVE FILTRATION AREA | | VALVE | DESIGN FLOW RATE* | | TURNOVER | | | | SAND REQUIRED | |
|--------------|---------------------------|------|----------------|-------------------|-----|----------|---------|------------|---------|---------------|-----|
| | ft.² | m² | | GPM | LPM | GALLONS | | KILOLITERS | | lbs. | kg |
| | | | | | | 8 hrs. | 10 hrs. | 8 hrs. | 10 hrs. | | |
| S210S | 2.20 | 0.20 | 1-½" Vari-Flo | 44 | 167 | 21,120 | 26,400 | 80 | 100 | 200 | 91 |
| S244S | 3.14 | 0.30 | 1-½" Vari-Flo | 62 | 235 | 29,760 | 37,200 | 113 | 141 | 300 | 136 |
| S244SV | 3.14 | 0.30 | 2" Slide Valve | 62 | 235 | 29,760 | 37,200 | 113 | 141 | 300 | 136 |
| S244SLV | 3.14 | 0.30 | Not Included | 62 | 235 | 29,760 | 37,200 | 113 | 141 | 300 | 136 |
| S310S | 4.91 | 0.46 | Not Included | 98 | 371 | 47,040 | 58,800 | 178 | 223 | 500 | 227 |

Patented Service-Ease Design



with unique folding ball joint design allows lateral assembly to be easily accessed for simple servicing.

*Based upon 20 GPM/ft², 814 LPM/m² (Maximum Allowable NSF Rating)



To take a closer look at Hayward Filters or other Hayward products, go to hayward.com or call 1-888-HAYWARD

